



MODEL	A	B	C	D	E	F	G	H	I	J
S65CD	26	22	46.25	39.375	15.875	13.875	8.375	45	45	55
S80CD	26	22	57.25	49.875	15.875	13.875	8.375	45	45	55
S100CD	26	22	67.75	60.375	18.375	16.375	8.375	45	45	55
S120CD	28	24	67.75	60.375	18.375	16.375	8.375	45	45	55

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS CONFIDENTIAL AND  
PROPRIETARY. THE CONTENTS OF THIS  
DRAWING ARE THE SOLE PROPERTY OF  
VAUGHN THERMAL CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
VAUGHN THERMAL CORPORATION IS  
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES  
DRAWN RP 9/3/2015  
CHECKED RP 2/14/2024  
LINEAR: 1 Decimal Place = ± 0.1  
2 Decimal Places = ± 0.01  
3 Decimal Places = ± 0.005  
ANGULAR: 1 Decimal Place = ± 1.0°  
2 Decimal Places = ± 0.5°  
INTERPRET GEOMETRIC  
TOLERANCING PER:  
MATERIAL:  
COMMENTS:  
ENG APPR.  
MFG APPR.  
Q.A.  
REV G  
TITLE: Vaughn Thermal Corp.  
Tank Assembly Aqua  
Booster Circulator CD  
Model Configurations  
SIZE DWG. NO. C V40A1240  
FINISH: PART NUMBER:  
SCALE: 1:8 SHEETS: 1

VAUGHN  
a nudyne company