



MODEL	A	B	C	D	E	F	G	H	I	J	K
	Jacket Diameter	Tank Diameter	Height to Pan	Height to T&P Relief Valve	Height to Immersion	Height to Top HX	Height to Bottom HX	Height to Combo Drain	Angle of T&P Relief Valve	Angle of Combo Drain	Angle of Immersion
65HX2	26	22	46.125	39.375	21.375	17.875	10.375	7.875	45	45	55
80HX2	26	22	57.125	49.875	21.375	17.875	10.375	7.875	45	45	55
80THX2	22.75	19	71.625	64.375	21.375	17.875	10.375	7.875	50	50	60
100HX2	26	22	67.375	60.375	21.375	17.875	10.375	7.875	45	45	55
120HX2	28	24	67.625	60.375	21.375	17.875	10.375	7.875	45	45	55

VAUGHN
a nudyne company

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS CONFIDENTIAL AND
PROPRIETARY. THE CONTENTS OF THIS
DRAWING ARE THE SOLE PROPERTY OF
VAUGHN THERMAL CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
VAUGHN THERMAL CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
DRAWN RP 6/24/2019
CHECKED RP 4/28/2020
ENG APPR.
MFG APPR.
Q.A.
TITLE: Vaughn Thermal Corp.
TITLE: Tank Assembly HX2
Configurations
SIZE DWG. NO. REV
C V41A0810 C
SCALE: 1:8 SHEETS: 1