



MODEL	A	B	C	D	E	F	G	H	I	J	K	L
	Jacket Diameter	Tank Diameter	Height to Pan	Height to T&P Relief Valve	Height to Immersion	Height to HX	Height to Cold In	Height to Drain	Angle of T&P Relief Valve	Angle of Drain	Angle of Cold In	Angle of Immersion
65DHX	26	22	46.125	39.375	13.75	10.375	8.375	7.875	45	45	55	55
80DHX	26	22	57.125	49.875	13.75	10.375	8.375	7.875	45	45	55	55
80TDHX	22.75	19	71.625	64.375	13.75	10.375	8.375	7.875	50	50	60	60
100DHX	26	22	67.375	60.375	13.75	10.375	8.375	7.875	45	45	55	55
120DHX	28	24	67.625	60.375	13.75	10.375	8.375	7.875	45	45	55	55

VAUGHN
a nudyne company

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS CONFIDENTIAL AND
PROPRIETARY. THE CONTENTS OF THIS
DRAWING ARE THE SOLE PROPERTY OF
VAUGHN THERMAL CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
VAUGHN THERMAL CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
DRAWN: RP 6/24/2019
CHECKED: RP 4/28/2020
ENG APPR.
MFG APPR.
Q.A.
INTERPRET GEOMETRIC
TOLERANCING PER:
MATERIAL: COMMENTS:
FINISH: PART NUMBER:
SIZE DWG. NO. REV
C V41A0830 C
SCALE: 1:8 SHEETS: 1

Vaughn Thermal Corp.

TITLE:
Tank Assembly DHX
Configurations